

Centring grommet F (fixed point)



Application range

- > For fastening facade claddings in combination with LT screws with head diameter 16 mm
- > To form fixed points

Properties

- > Grey coloured plastic
- > For panel thickness 2 / 4 / 6 / 8 mm
- > UV-resistant


Advantages

- > All holes in the facade cladding are produced with the same diameter (11 mm), which can be done efficiently at the shop floor
- > No rivet installation gauge, no drilling gauge necessary
- > Fast assembly in combination with LT screws
- > Easily revisionable panel fastening
- > The 0.5 collar of the grommet prevents direct contact between screw head and panel surface
- > The hole in the middle serves for the centered positioning of the screw

Note

Usability of grommets and LT screws must be agreed with the respective panel manufacturer. Please note the respective approval of the exterior wall cladding and the assembly instructions of the manufacturer.

Applications



Cross references

JT4-LT-3-5.5x25
 JT4-LT-2/6-6.0x50
 JT3-LT-3-5.5x30
 JF3-LT-2-5.5x30

Product online



Order description	Internal hole diameter [mm]	Pre-drilling diameter [mm]	Panel thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
EJOT centring grommet Ø 11/2 F	5.8	11.0	2.0	500		3010005700	4061245010212
EJOT centring grommet Ø 11/4 F	5.8	11.0	4.0	500		3010009700	4061245018478
EJOT centring grommet Ø 11/6 F	5.8	11.0	6.0	500		3010011700	4061245018454
EJOT centring grommet Ø 11/8 F	5.8	11.0	8.0	500		3010007700	4061245018492